

# PRODUCT SPECIFICATIONS

## LUBRICATING OILS

No.

SP 19 03 2002/RV0330-01

Date

19.03.2002

# TEBOIL 4T SUPERBIKE OIL SAE 10W-40

Motorcycle engine oil

CHARACTERISTICS	MIN.	TYPICAL	MAX.	METHOD
Density @20°C, kg/m <sup>3</sup>		862		ASTM D 4052
Viscosity @100°C, mm <sup>2</sup> /s	12,5	14,5	16,3	ASTM D 445
Viscosity @40°C, mm <sup>2</sup> /s		95		ASTM D 445
Viscosity index		159		ASTM D 2270
CCS @-25°C, mPa.s		6 350	7 000	ASTM D 5293
BPT @60.000 mPa.s, °C		-37	-30	ASTM D 4684
Pour point, °C		-42	-39	ASTM D 97
Evaporation loss, wt%		10	13	CEC-L-40-A-93
Flash point (COC), °C		240		ASTM D 92
TBN, mgKOH/g	7,5	8,5		ASTM D 4739
Sulfated ash, wt%		1,33		ASTM D 874
Ca, wt%		0,31		
Zn, wt%		0,16		
P, wt%		0,15		



Signature

### Note

These specifications are subject to change without infringement of signed agreements.