

PRODUCT SPECIFICATIONS

LUBRICATING OILS

No.

SP 19 03 2002/RV0330-01

Date

19.03.2002

TEBOIL 4T SUPERBIKE OIL SAE 10W-40

Motorcycle engine oil

| CHARACTERISTICS | MIN. | TYPICAL | MAX. | METHOD |
|--------------------------------------|------|---------|-------|---------------|
| Density @20°C, kg/m ³ | | 862 | | ASTM D 4052 |
| Viscosity @100°C, mm ² /s | 12,5 | 14,5 | 16,3 | ASTM D 445 |
| Viscosity @40°C, mm ² /s | | 95 | | ASTM D 445 |
| Viscosity index | | 159 | | ASTM D 2270 |
| CCS @-25°C, mPa.s | | 6 350 | 7 000 | ASTM D 5293 |
| BPT @60.000 mPa.s, °C | | -37 | -30 | ASTM D 4684 |
| Pour point, °C | | -42 | -39 | ASTM D 97 |
| Evaporation loss, wt% | | 10 | 13 | CEC-L-40-A-93 |
| Flash point (COC), °C | | 240 | | ASTM D 92 |
| TBN, mgKOH/g | 7,5 | 8,5 | | ASTM D 4739 |
| Sulfated ash, wt% | | 1,33 | | ASTM D 874 |
| Ca, wt% | | 0,31 | | |
| Zn, wt% | | 0,16 | | |
| P, wt% | | 0,15 | | |



Signature

Note

These specifications are subject to change without infringement of signed agreements.