

# PRODUCT SPECIFICATIONS

## LUBRICATING OILS

No.

SP 20 09 2001/RV0318-09

Date

20.09.2001

## TEBOIL DIAMOND SAE 5W-40

Gasoline engine oil

CHARACTERISTICS	MIN.	TYPICAL	MAX.	METHOD
Density @20°C, kg/m <sup>3</sup>		844		ASTM D 4052
Viscosity @100°C, mm <sup>2</sup> /s	12,5	14,0	16,3	ASTM D 445
Viscosity @40°C, mm <sup>2</sup> /s		90		ASTM D 445
Viscosity index		160		ASTM D 2270
CCS @-30°C, mPa.s		4 500	6 600	ASTM D 5293
BPT @60.000 mPa.s, °C		-46	-35	ASTM D 4684
Pour point, °C		-54	-45	ASTM D 97
Evaporation loss, wt%		8,0	13	CEC-L-40-A-93
Flash point (COC), °C		230		ASTM D 92
TBN, mgKOH/g	7,5	8,4		ASTM D 4739
Sulfated ash, wt%		1,32		ASTM D 874
Ca, wt%		0,31		
Zn, wt%		0,11		
P, wt%		0,10		

### Note

These specifications are subject to change without infringement of signed agreements.