

# PRODUCT SPECIFICATIONS

## LUBRICATING OILS

No.

SP 29 11 1999/RV0625-03

Date

29.11.1999

# TEBOIL HYDRAULIC ECO 68

Biodegradable special hydraulic oil

CHARACTERISTICS	MIN.	TYPICAL	MAX.	METHOD
Density @20°C, kg/m <sup>3</sup>		928		ASTM D 4052
Viscosity @100°C, mm <sup>2</sup> /s		13,0		ASTM D 445
Viscosity @40°C, mm <sup>2</sup> /s	61,2	68,0	74,8	ASTM D 445
Viscosity index		195		ASTM D 2270
Viscosity @50°C, mm <sup>2</sup> /s		47,0		ASTM D 445
Viscosity @±0°C, mm <sup>2</sup> /s		620		ASTM D 445
Viscosity @-10°C, mm <sup>2</sup> /s		1 350		ASTM D 445
Viscosity @-20°C, mm <sup>2</sup> /s		3 330	5 000	ASTM D 445
Pour point, °C		-48	-39	ASTM D 97
Flash point (PMC), °C	180	210		ASTM D 93
Sulfated ash, wt%		<0,01		ASTM D 874
P, wt%		0,008		
S, wt%		0,024		

### Note

These specifications are subject to change without infringement of signed agreements.