

# PRODUCT SPECIFICATIONS

## LUBRICATING OILS

No.

SP 29 11 1999/RV0652-04

Date

29.11.1999

# TEBOIL LARITA 10

## Hydraulic and circulation oil

| CHARACTERISTICS                      | MIN. | TYPICAL | MAX. | METHOD      |
|--------------------------------------|------|---------|------|-------------|
| Density @20°C, kg/m <sup>3</sup>     |      | 861     |      | ASTM D 4052 |
| Viscosity @100°C, mm <sup>2</sup> /s |      | 2,7     |      | ASTM D 445  |
| Viscosity @40°C, mm <sup>2</sup> /s  | 9,0  | 10,0    | 11,0 | ASTM D 445  |
| Viscosity index                      |      | 80      |      | ASTM D 2270 |
| Viscosity @50°C, mm <sup>2</sup> /s  |      | 7,0     |      | ASTM D 445  |
| Viscosity @±0°C, mm <sup>2</sup> /s  |      | 65      |      | ASTM D 445  |
| Viscosity @-20°C, mm <sup>2</sup> /s |      | 280     |      | ASTM D 445  |
| Pour point, °C                       |      | -51     | -42  | ASTM D 97   |
| Flash point (PMC), °C                | 140  | 160     |      | ASTM D 93   |
| Sulfated ash, wt%                    |      | 0,160   |      | ASTM D 874  |
| Ca, wt%                              |      | 0,006   |      |             |
| Zn, wt%                              |      | 0,056   |      |             |
| P, wt%                               |      | 0,044   |      |             |

### Note

These specifications are subject to change without infringement of signed agreements.